### DUCHESNE COUNTY MONUMENT SURVEY RECORD

DUCHESNE COUNTY 2½ DIA. ALUMINUM PIPE AND CAP MONUMENT AT 1/4

CORNER


N 68°36'43" E 75.62

NAIL AND WASHER ON RIGHT SIDE OF POWER POLE

T1S R1W

SEC 7 | SEC 8 SEC 18 | SEC 17

U.S.B.&M.



NORTH SCALE: 1"=30' 0' *30'* 

5/8"X24" REBAR WITH A 2½" DIA. DUCHESNE COUNTY ALUMINUM MONUMENT AT 1/4 CORNER

NAIL AND WASHER
ON LEFT SIDE OF
POWER POLE

00.08,28

10.2°

## NOTE: THE BASIS OF BEARINGS IS GEODETIC NORTH DERIVED FROM G.P.S. OBSERVATIONS AT A CONTROL POINT (SECTION CORNER) LOCATED AT LAT. 40"23"20.57790"N AND LONG. 110"01"46.98583"W USING THE UTAH STATE G.P.S. VIRTUAL REFERENCE STATION CONTROL NETWORK MAINTAINED AND OPERATED BY THE AUTOMATED GEOGRAPHIC REFERENCE CENTER DESCRIPTION OF CORNER EVIDENCE FOUND

NAIL AND WASHER
ON LEFT SIDE OF RR
TIE FENCE CORNER

FOUND MONUMENT SPIKE (HARROW TOOTH) AT POSITION OF SECTION CORNER



SET A 5/8"X24" REBAR WITH A 2½" BRASS DUCHESNE COUNTY MONUMENT AT THE POSITION OF THE SECTION CORNER AFTER ROAD CONSTRUCTION

# RIW < 018

### STATE PLANE COORDINATE DATA

(U.S. SURVEY FEET) . NAD83 UTAH CENTRAL ZONE N: 7319082.455 E: 2049845.386 NAVD88 EL: 5778.84'

40°24'12.70584" N LATITUDE: LONGITUDE: 110°01'47.18144" W

ELLIPSOID HEIGHT: 5724.54

(GEOID 03 CONUS)

PUBLIC LAND SURVEY SYSTEM GCDB ID NO.

UT300010S0010W0\_200500

#### **CERTIFICATION**

Jerry D. Allred \_ , Professional Land Surveyor, State of Utah, do hereby certify that I have performed or reviewed the work done on the diagrammed corner as reported on this recordation form and approve same

Date <u>28 FEB 2018</u>

Jerry D. Allred, Professional Land Surveyor Certificate No. 148951 Duchesne County Surveyor

